



# VARN Roller Lube

SPECIALITIES

## A lubricant for all types of rubber compounds

**ROLLER LUBE** lubricates rollers when printing half web or on printing units that require lubrication when running without ink.

**ROLLER LUBE** is safe for use on all types of rubber compound.

**ROLLER LUBE** can be sprayed on blankets at start-up to reduce tack.

**ROLLER LUBE** has a flashpoint >100°C and so is not classified as flammable or hazardous.

**ROLLER LUBE** allows ink to be applied without washing up roller train.



- **LUBRICATES ROLLERS WHEN PRINTING HALF WEB**



- **LUBRICATES UNITS WITHOUT RUNNING INK**



- **CAN BE SPRAYED OR APPLIED FROM WASH-UP BOTTLE**

- **SAFE ON ALL TYPES OF RUBBER COMPOUND**

- **FLASHPOINT >100°C**

FEATURES	ADVANTAGES	BENEFITS
CAN BE SPRAY APPLIED OR DIRECT FROM WASH-UP BOTTLE	● retards ink drying and skinning	● varied application
HIGH FLASHPOINT	● easy to apply	● safer pressroom environment
COMPATIBLE WITH ALL RUBBER COMPOUNDS	● fast, trouble-free start-ups	● safer usage on press

### DIRECTIONS

Apply sufficient **ROLLER LUBE** to wet all rollers.

**Must be re-applied every six hours (min). Do not allow to run dry.**

